

# Overview of Accelerator Systems at FRIB/NSCL

Alfonse N. Pham  
Michigan State University  
National Superconducting Cyclotron Laboratory


## Outline of Lecture

- Physics Research at FRIB and NSCL
  - Scientific Goals of FRIB/NSCL
  - Surveying Nuclear Landscape
- Accelerator System at FRIB
  - Specification of FRIB
  - Baseline Linac System
  - Superconducting RF Cavities
- ReAccelerator Facility at NSCL


## NSCL @ MSU




### National Superconducting Cyclotron Laboratory (NSCL)

- Established in 1963, the NSCL is the nation's largest nuclear science facility that is on a university campus
- Home to the K500-K1200 Coupled Cyclotron Facility and the A1900 Projectile Fragment Separator
- MSU #1 ranked Nuclear Physics Program in the Nation 
- Upgrade to the Facility for Rare Isotope Beams (FRIB) scheduled for 2022

## Scientific Goals of the Laboratory




- Properties of Atomic Nuclei
  - Develop a predictive model of nuclei and their interactions
- Nuclear Processes in Cosmos
  - Origin of the elements; processes in the cosmic cauldrons
  - Stellar evolution, stellar explosions, and compact stars
- Test Fundamental Laws of Nature
  - Effects of symmetry violations are amplified in certain nuclei
- Societal Applications and Benefits
  - Advancing technology in a wide range of fields such as medicine, energy, material sciences, and national security



# Periodic Table of Elements

- Elements ordered by atomic number (# protons)
- Maps chemical behavior of elements
- 118 elements identified, 98 naturally occurring




Dmitri I. Mendeleev (1834 – 1907)




J. Lothar Meyer (1830 – 1895)


# Table of Nuclides



Map nuclear (radioactive) behavior of nuclides




# Surveying the Nuclear Landscape



# NSCL/FRIB on the MSU Campus

- Upgrade of NSCL to FRIB will boost beam intensities and extend the varieties of rare isotope currently produced at the laboratory



## FRIB Specification


- Baseline Design of FRIB Driver Linac
  - Primary beams of stable ions up to Uranium-238
  - Ions are accelerated to energies  $\geq 200$  MeV/u
  - Beam power  $\leq 400$  kW on production target
  - Higher beam current by simultaneously accelerating several charge states (ex.  $^{238}\text{U}^{76+}$ , ...,  $^{238}\text{U}^{80+}$ ) while minimizing emittance
- Production Target and Fragment Separation System
  - Production and separation of Rare Isotope Beams (RIBs)
- Beam transport to experimental programs
  - Fast beams ( $\sim 0.5c$ ), Stopped beams ( $\sim eV$ ), Re-accelerated beams (0.3 – 12 MeV/u)



U.S. Department of Energy Office of Science  
National Science Foundation  
Michigan State University

A. N. Pham, 4/29/2016, Slide 9

## NSCL transition to FRIB



- Upgrade from NSCL to FRIB must minimize changes to existing experimental areas
- Allows post-production systems to be commissioned and ready before FRIB driver linac is completed



U.S. Department of Energy Office of Science  
National Science Foundation  
Michigan State University

A. N. Pham, 4/29/2016, Slide 10

## FRIB Challenges and Goals


- Robust ECR Ion Sources to deliver required beam currents
- Driver Linac accelerating all stable ions up to Uranium
- Produce beam on Production Target w/ spot size  $\sim 1$  mm diameter
  - Optimized for high production yield while minimizing damage to target
- Design will allow for future upgrades to the facility for
  - Higher beam energies with extra space to add more SRF cavities
  - Light-Ion Injector and Isotope Separation On-Line (ISOL) Facility
- FRIB will push the limits of superconducting RF cavity, ECR ion source, charge stripping, and rare isotope beam (RIB) production technology



U.S. Department of Energy Office of Science  
National Science Foundation  
Michigan State University

A. N. Pham, 4/29/2016, Slide 11

## FRIB Layout and Operation




U.S. Department of Energy Office of Science  
National Science Foundation  
Michigan State University

A. N. Pham, 4/29/2016, Slide 12




## Front End





- DC beam of high charge state up to  $^{238}\text{U}$  are produced by the ECRIS
- Selection through the Q/A spectrometer
- Selected ion species are accelerated, bunched, focused and matched in the Low Energy Beam Transport (LEBT) line into the RFQ
- RFQ focus and accelerate beams and the Medium Energy Transport (MEBT) matches beams into Linac Segment 1

## FRIB ECR Ion Sources



Machicoane G., et al., Status of ECR ion sources for the Facility for Rare Isotope Beams, (2015).




## FRIB SC-ECR Ion Source Parameters

	Required Charge States	Required Beam Current (pA)	Extraction Energy (keV/u)
<b>O</b>	> 3	122	12
<b>Ca</b>	> 8	51	12
<b>Kr</b>	> 14	50	12
<b>Xe</b>	> 20	24	12
<b>Pb</b>	> 27, 28	23	12
<b>U</b>	> 33, 34	16	12

Pushing the limits of current ECR ion source technology!

## Overview of SRF Cavities

Cavity Type	$\lambda/4$	$\lambda/4$	$\lambda/2$	$\lambda/2$
$\beta_{\text{opt}}$	0.041	0.085	0.285	0.530
f [MHz]	80.5	80.5	322	322
Aperture [mm]	30	30	40	40
$V_a$ [MV]	0.81	1.62	1.90	3.70
$E_p$ [MV/m]	30.8	33.5	33.3	26.5
$B_p$ [mT]	54.5	68.7	59.6	63.2
$T_c$ [K]	4.5	4.5	2.0	2.0
RF Drive [kW]	2	4	4	8
Number	19	115	80	162




Compton C., et al., Production Status of SRF Cavities for the FRIB project, SRF (2015)

Saito K., et al., FRIB Project: Moving to Production Phase, SRF (2015)



## Linac Segment 1

For  $^{238}\text{U}^{33+}$  and  $^{238}\text{U}^{34+}$ , acceleration from 0.5 MeV/u to ~16.6 MeV/u




80.5 MHz,  $\beta = 0.085$   
11 QW ( $\lambda/4$ ) Cryomodules

80.5 MHz,  $\beta = 0.041$   
3 QW ( $\lambda/4$ ) Cryomodules

## Inside a QW ( $\lambda/4$ ) Cryomodule


Superconducting Niobium QW Cavities operating at 80.5 MHz



Superconducting Solenoid magnets for beam focusing + dipole for steering

Beam position monitors (BPM) and other beam diagnostics


## Acceleration via RF Cavity




E-fields inside  $\lambda/4$   $\beta=0.085$  Cavity

B-fields inside  $\lambda/4$   $\beta=0.085$  Cavity


## Acceleration via RF Cavity



## Folding Segment 1




## Liquid Lithium Stripper



- Momozaki Y., Nolen J., et al., *Development of a liquid lithium thin film for use as a heavy ion beam stripper*, (2009).
- Marti F., et al., *Development of a Liquid Lithium Charge Stripper for FRIB*, (2015)

## Linac Segment 2


$U^{76+}$  to  $U^{80+}$ , acceleration from 16.6 MeV/u to  $\sim 150$  MeV/u



## Folding Segment 2


Since tunnel width limits the bending radius

- Large dipole fields are required
- Large momentum acceptance for multi-charge states beams in dispersive region
- Bends are dispersion free and isochronous to maintain tight particle bundle




## Linac Segment 3

U<sup>76+</sup> to U<sup>80+</sup>, acceleration from  
~150 MeV/u to ~200 MeV/u




- High cavity performance is needed for required energy delivered on production target
- Possible lower charge states if He gas stripper is used in place of Li stripper



Additional space for up to 12 Cryomodules!



322 MHz,  $\beta = 0.530$   
6 HW (N/2) Cryomodules

## Production Target and Separator




## Production Target

<b>Total Beam Power</b>	400 kW
<b>Total Power in Target</b>	90 kW
<b>Power Deposition</b>	60 MW/cm <sup>3</sup>
<b>Target Material</b>	Graphite MERSEN 2360
<b>Target Temp. Max.</b>	1900°C
<b>Slice Thickness</b>	0.1 to 10 mm
<b>Target Diameter</b>	30 cm
<b>Rotation Speed</b>	5500 rpm
<b>Max. Beam Extension</b>	50 mm



Pellemoine F., et al., *Development of a production target for FRIB: thermo-mechanical studies*, J Radioanal Nucl Chem (2014)



## Production Target



Avilov M., et al., *A 50-kW prototype of the high-power production target for the FRIB*, J Radioanal Nucl Chem (2014)




# End-to-End Beam Simulations




Challenge of a generation!

# FRIB Construction



# FRIB Construction



## FRIB Construction



U.S. Department of Energy Office of Science  
National Science Foundation  
Michigan State University

A. N. Pham, 4/29/2016, Slide 33

## FRIB Construction




U.S. Department of Energy Office of Science  
National Science Foundation  
Michigan State University

A. N. Pham, 4/29/2016, Slide 34

## ReAccelerator @ MSU NSCL


- ReA3 re-accelerates stopped/trapped ion beams to variable energies ( $\sim 0.3\text{--}3$  MeV/u for Uranium)
- It serves as a test bed for FRIB SRF technology
- Commissioning of ReA3 has been completed



U.S. Department of Energy Office of Science  
National Science Foundation  
Michigan State University

A. N. Pham, 4/29/2016, Slide 35

## ReAccelerator – Closer Look




U.S. Department of Energy Office of Science  
National Science Foundation  
Michigan State University

A. N. Pham, 4/29/2016, Slide 36




## ReA Upgrade Strategy



U.S. Department of Energy Office of Science  
National Science Foundation  
Michigan State University

A. N. Pham, 4/29/2016, Slide 37

## In Summary



U.S. Department of Energy Office of Science  
National Science Foundation  
Michigan State University

A. N. Pham, 4/29/2016, Slide 38

Thank you for your time!

Feel free to contact me  
[pham@nsl.msu.edu](mailto:pham@nsl.msu.edu)



U.S. Department of Energy Office of Science  
National Science Foundation  
Michigan State University

A. N. Pham, 4/29/2016, Slide 39