

Physics 905
Fundamentals of Accelerator Physics

Problem Set #7

April 21, 2016 · Due April 28, 2016

Steven Lund

25 points
Problem #1 Motion Near Synchronous Particle: Difference Eqns

In class we derived longitudinal difference equations

$$\Delta\phi_n - \Delta\phi_{n-1} = \frac{-2\pi N}{\gamma_{s,n-1}^3 \beta_{s,n-1}^2} \frac{\Delta W_{n-1}}{mc^2}$$

$$\Delta W_n - \Delta W_{n-1} = q E_{0n} L_n T_n(\beta_{sn}) [\cos(\phi_s + \Delta\phi_n) - \cos\phi_{s,n}]$$

$$\Delta\phi_n = \phi_n - \phi_{s,n}$$

$$\Delta W_n = W_n - W_{s,n}$$

2pts a) What term generates the nonlinearity? Why?

8pts b) Following steps in class, linearize the difference equations for small phase excursions about the synchronous particle and express the result as a 2x2 transfer matrix

$$\begin{bmatrix} \Delta\phi \\ \Delta W \end{bmatrix}_n = \begin{bmatrix} M_{2x2} \end{bmatrix} \begin{bmatrix} \Delta\phi \\ \Delta W \end{bmatrix}_{n-1} = \underline{M}_s \begin{bmatrix} \Delta\phi \\ \Delta W \end{bmatrix}_{n-1}$$

Show that $\det \underline{M}_s = 1$ and resolve \underline{M}_s as

$$\underline{M}_s = \begin{bmatrix} \phi & 0 \\ -1/f & 1 \end{bmatrix} \begin{bmatrix} 1 & d \\ 0 & 1 \end{bmatrix}$$

Thin lens drift

and identify

$d = \text{drift length}$
 $1/f = \text{inverse focal length.}$

If $d < 0$ is this a problem? Will the system still focus? Why?

10pts c) Assume negligible synchronous particle energy gain and a regular periodic lattice:

$$\beta_{s,n} = \beta_s = \text{const} \quad \Rightarrow \quad \gamma_{s,n} = \gamma_s = \text{const}$$

$$E_{0n} = E_0 = \text{const}$$

$$L_n = L = \text{const}$$

$$T_n = T = \text{const}$$

$$\phi_{s,n} = \phi_s = \text{const}$$

2/

Define a synchronous phase advance using M_s in part b) and calculate the synchronous phase advance. $\bar{\sigma}_s =$ phase advance per cell L . Compare the result to the synchrotron wavenumber k_s calculated in class. For small phase advance per cell. Should you expect the relationship obtained? Why?

15pts
d)

Suppose we apply the linear equations in the limit of small acceleration within the continuous approximation derived in class. For an orbit with max phase extent $\Delta\phi_0$ find an expression for the longitudinal emittance in $\Delta\phi, \Delta W$ phase-space with

$$\pi E_s = \text{Area ellipse in } \Delta\phi - \Delta W$$

The units of E_s will be radians-eV (energy). How should we scale this result to measure E_s in $\Delta t, \Delta W$ phase-space to measure area in eV-sec.?

30 points

Problem #2

Hamiltonian Form of Synchrotron Equations of Motion

In class we showed that in the continuous approximation, that the longitudinal equations of motion about the synchronous particle are

$$\frac{d\phi}{ds} = -AW$$

$$\frac{dW}{ds} = B [\cos\phi - \cos\phi_s]$$

$$W = \frac{\Delta W}{mc^2}$$

$$A = \frac{2\pi}{\lambda + (\gamma_s \beta_s)^3}$$

$$B = \frac{gE_0 T}{mc^2}$$

10pts

- a) Find a Hamiltonian $H(\phi, p_\phi)$ and conjugate "momentum" variable p_ϕ such that the equations of motion are given by:

$$\frac{d\phi}{ds} = \frac{\partial H}{\partial p_\phi}$$

$$\frac{d p_\phi}{ds} = -\frac{\partial H}{\partial \phi}$$

Compare H to H_ϕ constructed in class.

10pts

- b) Consider a distribution of particles evolving according to H in longitudinal phase-space. Neglect particle-particle interactions.

(not in formulation). A smooth distribution $f(\phi, p_\phi, s) \geq 0$ must satisfy

$$\frac{\partial f}{\partial s} + \frac{\partial}{\partial \phi} \left(\frac{d\phi}{ds} f \right) + \frac{\partial}{\partial p_\phi} \left(\frac{d p_\phi}{ds} f \right) = 0$$

since "probability" must flow somewhere. Show for our nonlinear longitudinal dynamics that

$$\left. \frac{d f}{ds} \right|_{\text{particle trajectory}} = 0$$

Explain how this implies that the total phase-space weight of particles at a given density is constant in the nonlinear evolution. You may want to read about Liouville's Theorem of noninteracting particles in statistical mechanics if you need help.

5 pts

c) If $\gamma\beta_s \neq \text{const}$ but vary slowly to maintain validity of the continuous formulation will H be constant? Why? [keep all other factors constant in s]
 $T, \phi_s, E_0, \lambda r, \phi_s$

5 pts

d) If the phase excursion is small ($\phi = \phi_s + \Delta\phi$; $\Delta\phi$ small) with $\gamma\beta_s$ slowly varying, derive a 2nd order differential equation for the evolution of $\Delta\phi$. Do you expect this equation to have a conserved longitudinal emittance? Why?

For this part start from the continuous formulation with

$$(\gamma\beta_s)^3 \frac{d}{ds} (\phi - \phi_s) = -\frac{z\pi}{\lambda r} \frac{\Delta W}{mc^2}$$

$$\frac{d}{ds} \Delta W = g E_0 T (\cos\phi - \cos\phi_s)$$

Take $\lambda r, E_0, T, \phi_s$ to be constants.

Write results using $\beta_s^2 = \frac{z\pi g E_0 T \sin(-\phi_s)}{\lambda r \gamma_s^3 \beta_s^3 mc^2}$

Problem #3. RF Phase Choices. ^{10 points}

✓

In class, for the continuous model we showed that where

$$E_z(r=0, z=0, t=0) = E_0 \cos \phi_s > 0 \Rightarrow \text{accel} \quad E_0 > 0$$
$$< 0 \Rightarrow \text{deaccel.}$$

and where

$$V(\phi) = B(\sin \phi - \phi \cos \phi_s) \quad B = \frac{qE_0 T}{mc} > 0$$

has concavity

$$\frac{d^2 V(\phi)}{d\phi^2} \Big|_{\phi=\phi_s} > 0 \Rightarrow \text{stability (focusing)}$$
$$< 0 \Rightarrow \text{instability (defocusing)}$$

locally about the synchronous particle

Use these to argue:

2pts a) Range of ϕ_s for deacceleration and focusing?

2pts b) Range of ϕ_s for acceleration and defocusing?

Separately, from continuous model

2pts c) What value of ϕ_s will provide max longitudinal focusing and acceptance? why? Does this allow acceleration?

"Fast Rotation"

4pts d) Consider a bunch with weak or no accel in the continuous model. Filling a small phase-width of the bucket.

If E_0 suddenly jumps argue what will happen to the longitudinal phase-phase-space ellipse. At what propagation length will the bunch have shortest phase width? Use the synchrotron wavenumber k_s to estimate. What value of ϕ_s should be chosen

30 pts. ✓

Problem #4 Pillbox Cavity

Consider a pillbox cavity of radius $r_c = \frac{75 \text{ cm}}{2}$ and axial length $l = 50 \text{ cm}$.

2 pts a) What is the resonant freq. of the fundamental TM_{010} mode?

2 pts b) What is the resonant freq. of the next highest TM_{011} mode?

6 pts c) What value of β will have a transit-time-factor of $T = 1/2$ for this cavity, operating at the fundamental frequency? Use the single-gap transit-time-factor derived in class. Feel free to use a numerical root finder. β should be greater than this value for $T > 1/2$.

5 pts d) Explain how the cavity might be modified to increase the acceleration efficiency (larger T for given β greater than value found in c). Qualitative only.

15 pts e) For the cavity operating at the fundamental. Assume an RF voltage $V_0 = E_0 l = 500 \text{ kV}$ and CU with a conductivity of $\frac{1}{\sigma} = 1.7 \times 10^{-8} \text{ } \Omega \cdot \text{m}$, calculate:

U = stored EM energy

R_{surf} = RF surface resistance

$\langle P_{\text{loss}} \rangle_{\text{avg}}$ = Avg. power loss.

Q = Quality factor.

R_s = shunt impedance

Use formulas derived in the class notes.